



CORDLESS SYSTEMS




Cordless Rotary Hammers

Cordless rotary hammer TE 2-A22	Page 54
22V cordless rotary hammer featuring low weight for superior handling in serial applications TE 4-A22	Page 54
36V cordless rotary hammer with superior performance TE 6-A36-AVR	Page 55


Cordless Combihammers

Cordless combihammer TE 30-A36	Page 56
--------------------------------	---------


Drills, Impact Drivers and Wrenches

Subcompact cordless drill driver SF 2-A	Page 57
22V cordless drill driver SF 8M-A22	Page 57
Compact cordless drill driver SFC 14-A	Page 58
Cordless hammer drill driver SFH 14-A	Page 58
22V cordless drill driver SF 10W-A22	Page 59
Compact cordless drill driver SFC 22-A	Page 59
22V hammer drill driver SFH 22-A	Page 60
Compact class cordless 22V impact driver SID 22-A	Page 60
22V cordless impact wrench SIW 22-A	Page 62
22V cordless high-torque impact wrench SIW 22T-A 1/2"	Page 62


Cordless saws

22V cordless circular saw featuring low weight, for cutting materials up to 57 mm thick SCW 22-A	Page 63
Cordless circular saw SCM 22-A	Page 63
Cordless reciprocating saw WSR 22-A	Page 64
Cordless reciprocating saw WSR 36-A	Page 64


Cordless angle grinders

Cordless angle grinder AG 125-A22	Page 66
-----------------------------------	---------


Cordless Lamps

Cordless 14V LED work light/lamp SFL 14-A	Page 67
Cordless lamp SFL 22-A	Page 67
Cordless lamp SFL 36-A	Page 67


Cordless Dispensers

Dispenser HDE 500-A22	Page 68
-----------------------	---------

Inserts

HSS ground drill bit set for drilling small-diameter holes in metal HSS sets	Page 69-77
--	------------


Batteries, Chargers and Accessories

Batteries	Page 78-82
Accessories For UCD cordless tools, batteries and chargers	Page 83
On-board vacuum system for convenient dust collection TE DRS-4-A	Page 84
On-board vacuum system for convenient dust collection TE DRS-6-A	Page 84


Cordless Vacuum Cleaners

Universal wet and dry cordless and corded vacuum cleaner VC 20-U(M)-Y	Page 85
Universal wet and dry cordless and corded vacuum cleaner VC 40-U(M)-Y	Page 85


Cordless Drywall Screwdrivers

Cordless drywall screwdriver SD 5000-A22	Page 87
--	---------


Cordless Metal Construction Screwdrivers

Cordless metal construction screwdriver ST 1800-A22	Page 87
---	---------

Cordless rotary hammer TE 2-A22



KEY APPLICATIONS & ADVANTAGES

- Construction: light-duty drilling in concrete and masonry
- Interior finishing: installing partition walls and suspended ceilings
- Metal fabricators: fastening metal items such as handrails, staircases, sun blinds, barriers, etc.
- Cordless freedom with the performance of a corded tool
- Compact size and light weight for superior handling



Technical data

Rated voltage	21.6 V
Single impact energy	1.5 J
Full hammering frequency	5040 impacts/minute
Rotation speed gear 1 under no load	1090 rpm
Triaxial vibration value for hammer drilling into concrete (ah,HD) ¹⁾	15 m/s ²
Dust removal module	TE DRS-S (optional)
Weight according to EPTA Procedure 01/2003	2.7 kg
A-weighted emission sound power level ²⁾	103 dB (A)
A-weighted emission sound pressure level ²⁾	92 dB (A)
Battery charge status display	Yes

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745

Ordering designation	Package contents	Sales pack quantity	Item number
Kit TE 2-A22 + AG 125-A22 + SFC 22-A	1x Cordless rotary hammer TE 2-A22 assy, 1x Cordless angle grinder AG 125-A22, 1x Protective cover 125-P88 assy, 1x Clip-on front cover 125, 1x Cordl. compact drill driver SFC 22-A CE, 1x Battery charger C 4/36-90 230V, 1x Battery pack B 22/2.6 Li-ion, 1x Battery pack B 22/5.2 Li-ion, 1x Hammer drill bit TE-C(2) 5/11, 2x Hammer drill bit TE-C(2) 6/16, 1x Hammer drill bit TE-C(2) 8/16, 1x Hammer drill bit TE-C(2) 10/16, 1x Hammer drill bit TE-C(2) 12/16, 1x Bit set S-BSC UNI 50/2" T (6) Bulk, 25x Cutting disc AC-D 125 (5") SP CAG, 1x Case	1 pc	3545207
TE 2-A22 box	1x Cordless rotary hammer TE 2-A22 assy	1 pc	2021422
TE 2-A22 cas	1x Cordless rotary hammer TE 2-A22 assy, 1x Case	1 pc	2021420

22V cordless rotary hammer featuring low weight for superior handling in serial applications TE 4-A22



KEY APPLICATIONS & ADVANTAGES

- Drilling and hammer drilling in concrete and masonry
- Drilling in concrete in clean areas using the integrated dust removal system (DRS-4-A)
- Occasional drilling in wood and steel with optional chuck adapter
- Excellent performance-to-weight ratio and compact design
- Virtually dustless drilling with the DRS-4-A dust removal system



Technical data

Rated voltage	21.6 V
Single impact energy	2 J
Full hammering frequency	5200 impacts/minute
Rotation speed gear 1 under no load	1090 rpm
Triaxial vibration value for hammer drilling into concrete (ah,HD) ¹⁾	11 m/s ²
Dust removal module	Yes (optional)
Weight according to EPTA Procedure 01/2003	3.3 kg
A-weighted emission sound power level ²⁾	99 dB (A)
A-weighted emission sound pressure level ²⁾	88 dB (A)
Base material	Concrete, Masonry, Wood, Steel

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745

Ordering designation	Package contents	Sales pack quantity	Item number
TE 4-A22 cas	1x Cordless rotary hammer TE 4-A22 02, 1x Case	1 pc	2098475

36V cordless rotary hammer with superior performance TE 6-A36-AVR



KEY APPLICATIONS & ADVANTAGES

- Drilling and hammer drilling in concrete and masonry
- Occasional drilling in wood and steel with optional quick-release chuck
- Screwdriving using the special bit holder with TE-C (SDS Plus) connection end
- Ergonomically designed D-grip for comfortable use over long periods
- Robustly built and superbly engineered for cordless optimization

Technical data

Rated voltage	36 V
Single impact energy	2 J
Full hammering frequency	5283 impacts/minute
Rotation speed gear 1 under no load	1040 rpm
Triaxial vibration value for hammer drilling into concrete (ah,HD) ¹⁾	9 m/s ²
Active Vibration Reduction	Yes
Dust removal module	TE DRS-6-A (optional)
Weight according to EPTA Procedure 01/2003	4 kg
A-weighted emission sound power level ²⁾	99 dB (A)
A-weighted emission sound pressure level ²⁾	88 dB (A)

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745



CPC AVR

3

Ordering designation	Package contents	Sales pack quantity	Item number
TE 6-A36-AVR cas	1x Cordless rotary hammer TE 6-A36-AVR assy, 1x Case	1 pc	2040299

Accessories for Cordless Rotary Hammers

Ordering designation	TE 6-A36-AVR	TE 2-A22	TE 4-A22	Sales pack quantity	Item number
Battery charger C 4/36-350 230V box				1 pc	2028875
5.2 Fast Charge Combo				1 pc	3545209
Battery charger C 4/36-90 230V box				1 pc	2015761
Battery pack B 22/2.6 Li-ion				1 pc	2110532
Battery pack B 22/3.3 Li-ion				1 pc	2007431
Battery pack B 22/5.2 Li-ion				1 pc	2110409
Cordless lamp SFL 22-A box				1 pc	426117
Cordless lamp SFL 36-A box				1 pc	2026734
Dust removal system TE DRS-6-A box				1 pc	2040914
Quick-release chuck TE 2M/7C/7A/6A Li Drilling in wood or metal				1 pc	224119

Cordless combihammer TE 30-A36



KEY APPLICATIONS & ADVANTAGES

- Cordless combihammer for higher productivity through greater mobility

Technical data

Rated voltage	36 V
Single impact energy	3.6 J
Full hammering frequency	4500 impacts/minute
Rotation speed gear 1 under no load	850 rpm
Active Torque Control	Yes
Active Vibration Reduction	Yes
Dust removal module	TE DRS-S (optional)
Weight according to EPTA Procedure 01/2003	5.5 kg
A-weighted emission sound power level ¹⁾	105 dB (A)
A-weighted emission sound pressure level ¹⁾	94 dB (A)

¹⁾ according to EN 60745



CPC



SDS plus

Ordering designation	Package contents	Sales pack quantity	Item number
TE 30-A36 cas	1x Cordless combihammer TE 30-A36, 1x Case	1 pc	2029312

Accessories for Cordless Combihammers

Ordering designation		TE 30-A36	Sales pack quantity	Item number
Quick-release chuck TE 16/TE 30 Drilling in wood or metal		■	1 pc	282341
Cordless lamp SFL 36-A box		■	1 pc	2026734

Subcompact cordless drill driver with 12V Li-ion battery and 10 mm keyless chuck for light-duty applications SF 2-A



KEY APPLICATIONS & ADVANTAGES

- Driving self-tapping screws up to 4.8 mm diameter in metal
- Driving screws up to 6 mm diameter in wood
- Drilling with HSS bits up to 8 mm diameter in metal
- Ergonomic grip and perfect balance for maximum working comfort
- High productivity thanks to a drilling speed of up to 1,500 /min

Technical data

Battery type	Li-ion
Brushless motor	No
Number of gears	2
Rotation speed gear 1 under no load	400 rpm
Rotation speed gear 2 under no load	1500 rpm
Max. torque	24 Nm
Max. torque hard joint	24 Nm
Max. torque	12 Nm (soft joint), 24 Nm (hard joint)
Max. torque (soft joint)	12 Nm
Weight according to EPTA Procedure 01/2003	1.1 kg

Ordering designation	Package contents	Sales pack quantity	Item number
SF2 Start Up Kit	1x Cordless drill driver SF 2-A assy, 1x Case, 1x Battery charger C 4/12-50 230V, 1x Battery pack B 12/2.6	1 pc	3539528
SF 2 Combo P	1x Cordless drill driver SF 2-A assy, 1x Case, 1x Battery pack B 12/2.6, 1x Battery charger C 4/12-50 230V, 1x Bit set S-BSC+ UNI 25/1" T (10)	1 pc	3558631
SF2 Add on Kit	1x Cordless drill driver SF 2-A assy, 1x Case, 2x Battery pack B 12/2.6, 1x Adapter CA-B12 assy, 1x Holster	1 pc	3539530
M&E SF2 & Pipersings Combo	1x Cordless drill driver SF 2-A assy, 1x Case, 2x Battery pack B 12/2.6, 1x Battery charger C 4/12-50 230V, 10x Pipe ring MP-PI 4" M8/M10 assy, 1x Holster	1 pc	3539532
SF2 Two Combo	2x Cordless drill driver SF 2-A assy, 2x Case, 3x Battery pack B 12/2.6, 1x Battery charger C 4/12-50 230V	1 pc	3539531
SF 2-A cas	1x Cordless drill driver SF 2-A assy, 1x Case	1 pc	2090912

Ultimate class 22V cordless drill driver with four-speed gearing and secure chuck for reduced drill bit slippage and high performance in metal drilling applications SF 8M-A22



KEY APPLICATIONS & ADVANTAGES

- Drilling in metal with HSS bits up to 20 mm diameter
- Drilling with stepper bits up to 40 mm diameter in metal sheet up to 3 mm
- Cutting holes in metal using hole saws up to 102 mm diameter
- Extremely durable 4-speed, all-metal gearing providing the optimum speeds for various drilling applications in metal
- Specialised chuck optimised for metal drilling, with "self-tightening" function to prevent drill bit slippage during operation

Technical data

Battery type	Li-ion
Brushless motor	No
Number of gears	4
Rotation speed gear 1 under no load	320 rpm
Rotation speed gear 2 under no load	550 rpm
Rotation speed gear 3 under no load	1250 rpm
Max. torque	84 Nm
Rotation speed gear 4 under no load	2150 rpm
Max. torque hard joint	84 Nm
Max. torque	50 Nm (soft joint), 84 Nm (hard joint)



Ordering designation	Package contents	Sales pack quantity	Item number
SF 8M-A22 cas	1x Cordless drill driver SF 8M-A22 assy, 1x Hook wrench SF 8M-A22, 1x Case	1 pc	2061285

Compact cordless drill driver with 22V Li-ion battery and 13 mm keyless chuck for light-duty applications SFC 14-A



KEY APPLICATIONS & ADVANTAGES

- Driving screws up to 6 mm diameter in wood
- Driving screws for plastic anchors up to 8 mm diameter
- Driving self-tapping screws up to 4.8 mm diameter in metal
- Very compact design for best-possible access in tight corners
- Compact and durable Hilti Lithium CPC battery for high performance and long life

Technical data

Battery type	Li-ion
Brushless motor	No
Number of gears	2
Rotation speed gear 1 under no load	500 rpm
Rotation speed gear 2 under no load	1700 rpm
Max. torque	45 Nm
Max. torque hard joint	45 Nm
Max. torque	24 Nm (soft joint), 45 Nm (hard joint)
Max. torque (soft joint)	24 Nm
Weight according to EPTA Procedure 01/2003	1.5 kg

Ordering designation	Package contents	Sales pack quantity	Item number
SFC 14-A Base Kit (1) - New	1x Cordl. compact drill driver SFC 14-A CE, 1x Case, 2x Battery pack B 14/1.6 Li-Ion, 1x Battery charger C 4/36-90 230V, 1x Bit set S-BSC UNI 50/2" T (6) Bulk	1 pc	3508819
SFC 14-A Base Kit (2) - New	1x Cordl. compact drill driver SFC 14-A CE, 1x Case, 2x Battery pack B 14/1.6 Li-Ion, 1x Battery charger C 4/36-90 230V, 1x Twist drill bit HSS 2-8	1 pc	3508820
SFC 14-A cas	1x Cordl. compact drill driver SFC 14-A CE, 1x Case	1 pc	429275

Cordless hammer drill driver SFH 14-A



KEY APPLICATIONS & ADVANTAGES

- Hammer drilling in diameters up to 14 mm in brick, masonry and soft concrete
- Cutting recesses and through-holes with hole saws
- Driving heavy-gauge wood screws
- Highest battery capacity (3.3 Ah)
- Outstanding performance in heavy applications (40 Nm soft joint torque)

Technical data

Battery type	Li-ion
Brushless motor	No
Number of gears	3
Rotation speed gear 1 under no load	400 rpm
Rotation speed gear 2 under no load	1300 rpm
Rotation speed gear 3 under no load	2250 rpm
Max. torque	70 Nm
Max. torque hard joint	70 Nm
Max. torque	40 Nm (soft joint), 70 Nm (hard joint)
Max. torque (soft joint)	40 Nm

Ordering designation	Package contents	Sales pack quantity	Item number
SFH 14-A Base Kit (1) - New	1x Cordl. ham. dr. driver SFH 14-A CE, 2x Battery pack B 14/3.3 Li-Ion, 1x Battery charger C 4/36-90 230V, 1x Toolbag small	1 pc	3508821
SFH 14-A Base Kit (2) - New	1x Cordl. ham. dr. driver SFH 14-A CE, 2x Battery pack B 14/3.3 Li-Ion, 1x Battery charger C 4/36-90 230V, 1x Twist drill bit HSS 2-8	1 pc	3508822
SFH 14-A box	1x Cordl. ham. dr. driver SFH 14-A CE	1 pc	429272

Ultimate class 22V cordless drill driver with Active Torque Control and four-speed gearing for high torque in demanding applications in wood and other materials SF 10W-A22


CPC

KEY APPLICATIONS & ADVANTAGES

- Extremely powerful: high torque for the toughest applications
- Extremely durable 4-speed all-metal gearing for high torque
- Metal chuck sleeve for better handling
- Drilling with auger bits up to 50 mm diameter in wood
- Cutting recesses and through holes using hole saws up to 152 mm diameter

Technical data

Battery type	Li-ion
Number of gears	4
Rotation speed gear 1 under no load	310 rpm
Rotation speed gear 2 under no load	530 rpm
Rotation speed gear 3 under no load	1210 rpm
Rotation speed gear 4 under no load	2100 rpm
Max. torque	120 Nm
Max. torque hard joint	120 Nm
Max. torque	72 Nm (soft joint), 120 Nm (hard joint)
Max. torque (soft joint)	72 Nm

3

Ordering designation	Package contents	Sales pack quantity	Item number
SF 10W-A22 cas	1x Cordless drill driver SF 10W-A22 assy, 1x Case	1 pc	2061286

Compact cordless drill driver with 22V Li-ion battery and 13 mm keyless chuck for light- and medium-duty applications SFC 22-A



KEY APPLICATIONS & ADVANTAGES

- Hole sawing in diameters up to 82 mm
- Driving screws up to 8 mm diameter in wood
- Drilling with auger and spade bits up to 26 mm diameter in wood
- Lightweight and compact
- Ergonomically designed grip for maximum working comfort

Technical data

Battery type	Li-ion
Number of gears	2
Rotation speed gear 1 under no load	600 rpm
Rotation speed gear 2 under no load	1800 rpm
Max. torque	55 Nm
Max. torque hard joint	55 Nm
Max. torque	28 Nm (soft joint), 55 Nm (hard joint)
Max. torque (soft joint)	28 Nm
Weight according to EPTA Procedure 01/2003	1.7 kg
Torque range (adjustable)	2 - 10 Nm

Ordering designation	Package contents	Sales pack quantity	Item number
SFC 22-A box	1x Cordl. compact drill driver SFC 22-A CE	1 pc	435849
SFC 22-A cas	1x Cordl. compact drill driver SFC 22-A CE, 1x Case	1 pc	2006480

Power class cordless 22V hammer drill driver for medium- to heavy-duty applications in masonry, wood, metal and other materials SFH 22-A



KEY APPLICATIONS & ADVANTAGES

- Hammer drilling in diameters up to 14 mm in brick, masonry, sand-lime block and aerated concrete
- Drilling with auger and spade bits up to 32 mm diameter in wood
- Drilling with high torque and speed in diameters up to 13 mm in metal
- Superior performance and battery capacity in the 22 volt class
- Outstanding performance-to-size ratio

Technical data

Battery type	Li-ion
Brushless motor	No
Number of gears	3
Rotation speed gear 1 under no load	370 rpm
Rotation speed gear 2 under no load	1250 rpm
Rotation speed gear 3 under no load	2140 rpm
Max. torque	84 Nm
Max. torque hard joint	84 Nm
Max. torque	50 Nm (soft joint), 84 Nm (hard joint)
Max. torque (soft joint)	50 Nm



Ordering designation	Package contents	Sales pack quantity	Item number
Foreman Kit	1x Cordl. ham. dr. driver SFH 22-A CE/JP, 1x Case, 1x Bimetal hole saw 19mm-3/4" MultiCut, 1x Bimetal hole saw 22mm-7/8" MultiCut, 1x Bimetal hole saw 25mm-1" MultiCut, 1x Bimetal hole saw 35mm-1 3/8" MultiCut, 1x Bimetal hole saw 51mm-2" MultiCut, 1x Bimetal hole saw 68mm-2 11/16" MultiCut, 1x Hole saw arbor, 2x Battery pack B 22/5.2 Li-ion, 1x Battery charger C 4/36-90 230V, 1x Stepped drill bit 4-20, 1x Twist drill bit HSS 1-10, 1x Masonry drill bit MDB 4,5,6,8,10 kit, 1x Bit set S-BSC+ UNI 25/1" T (10)	1 pc	3545212
SFH 22-A box	1x Cordl. ham. dr. driver SFH 22-A CE/JP	1 pc	290212
SFH 22-A cas	1x Cordl. ham. dr. driver SFH 22-A CE/JP, 1x Case	1 pc	290211

Compact class cordless 22V impact driver with hexagonal chuck for medium-duty applications in wood, metal and other materials SID 22-A



KEY APPLICATIONS & ADVANTAGES

- Driving HUS screw anchors up to 6 mm in masonry and concrete
- Driving 8 mm and 10 mm HRD frame anchors in masonry and concrete
- Driving lag bolts up to 8 mm in wood
- Compact design allows easy use in tight corners and wherever space is limited
- Perfect balance and low weight










Technical data

Battery type	Li-ion
Brushless motor	Yes
Number of gears	3
Max. torque	165 Nm
Rotation speed under no load, setting 1	1000 rpm
Rotation speed under no load, setting 2	1500 rpm
Rotation speed under no load, setting 3	2500 rpm
Weight according to EPTA Procedure 01/2003	1.5 kg
Battery charge status display	Yes
Cordless Power Care - CPC	Yes



Ordering designation	Package contents	Sales pack quantity	Item number
SID 22-A box	1x Cordl. impact driver SID 22-A	1 pc	2006071
SID 22-A cas	1x Cordl. impact driver SID 22-A, 1x Case	1 pc	2006073

Accessories for Cordless Drills and Impact Drivers, Wrenches

Ordering designation		SF 8M-A22	SF 2-A	SFH 14-A	SF 10W-A22	SFH 22-A	SFC 22-A	SID 22-A	SIW 22-A	SIW 22T-A 1/2"	Sales pack quantity	Item number
Battery charger C 4/36-350 230V box		■				■			■	■	1 pc	2028875
5.2 Fast Charge Combo		■			■	■	■				1 pc	3545209
Battery charger C 4/12-50 230V box			■								1 pc	2077004
Battery charger C 4/36-90 230V box		■		■			■	■			1 pc	2015761
Battery pack B 12/2.6			■								1 pc	2077976
Battery pack B 14/3.3 Li-Ion				■							1 pc	426175
Battery pack B 22/1.6 Li-Ion							■	■			1 pc	426177
Battery pack B 22/2.6 Li-Ion						■	■				1 pc	2110532
Battery pack B 22/3.3 Li-Ion						■	■		■	■	1 pc	2007431
Battery pack B 22/5.2 Li-Ion		■			■	■	■				1 pc	2110409
Cordless lamp SFL 14-A box				■							1 pc	426115
Cordless lamp SFL 22-A box						■	■				1 pc	426117

Universal class 22V cordless impact wrench with 1/2" ball detent pin connection end, brushless motor and three-speed gearing for reliable anchoring and bolting SIW 22-A



KEY APPLICATIONS & ADVANTAGES

- Tightening and releasing high-strength nuts and bolts from M6 to M12
- Setting HSA stud anchors in the sizes M8 to M12 with the S-TB torque bar
- Driving 6 mm and 8 mm HUS3 screw anchors in concrete
- High-efficiency brushless motor for long life and more work per charge
- Compact design allows easy use in tight corners and wherever space is limited

Technical data

Battery type	Li-ion
Brushless motor	Yes
Number of gears	3
Max. torque	200 Nm
Rotation speed under no load, setting 1	1000 rpm
Rotation speed under no load, setting 2	1500 rpm
Rotation speed under no load, setting 3	2300 rpm
Weight according to EPTA Procedure 01/2003	1.5 kg
Battery charge status display	Yes
Cordless Power Care - CPC	Yes

Ordering designation	Package contents	Sales pack quantity	Item number
SIW 22-A 1/2" box	1x Cordl. impact wrench SIW 22-A 1/2"	1 pc	2006079
SIW 22-A 1/2" cas	1x Cordl. impact wrench SIW 22-A 1/2", 1x Case	1 pc	2006081

Power class 22V cordless high-torque impact wrench with 1/2" ball detent pin connection end and robust anvil for demanding applications in the steel, metal and wood structural trades SIW 22T-A 1/2"



KEY APPLICATIONS & ADVANTAGES

- Driving HUS3 screw anchors from 8 mm to 14 mm diameter in concrete
- Tightening and releasing nuts and bolts from M12 to M24
- Assembling steel profiles, timber or pre-cast concrete components
- Compact design with excellent balance for precise handling
- 1/2" square drive with heavy-duty ball-notch retention for security and quick socket changing

Technical data

Battery type	B 22/2.6 Li-ion
Number of gears	1
Max. torque	450 Nm
Rotation speed under no load, setting 1	2000 rpm
Weight according to EPTA Procedure 01/2003	3 kg
Battery charge status display	Yes
Cordless Power Care - CPC	Yes
Tightening universal anchors (HUD) - max. dia.	14 mm
Tightening universal anchors (HUD) - related max. length	70 mm
A-weighted emission sound power level ¹⁾	106.5 dB (A)

¹⁾ according to EN 60745

Ordering designation	Package contents	Sales pack quantity	Item number
SIW 22T-A kit	1x Cordl. impact wrench SIW 22T-A assy, 1x Impact socket S-NSD 1/2"-13 S, 1x Impact socket S-NSD 1/2"-15 S, 1x Impact socket S-NSD 1/2"-13 L, 1x Impact socket S-NSD 1/2"-15 L, 1x Case	1 pc	409459

22V cordless circular saw featuring low weight, for cutting materials up to 57 mm thick SCW 22-A


CPC

KEY APPLICATIONS & ADVANTAGES

- General construction: cutting formwork boards, OSB, plywood, chipboard, plastics, rafters and battens
- Interior finishing: cutting drywall board, cement board, MDF and HDF
- Cutting formwork boards, planks, battens, OSB, chipboard, plywood sheets and plastics
- Impressive cutting performance for a tool of this size and weight
- Compatible with all Hilti 22V batteries, accurate battery charge status display

Technical data

Rated voltage	21.6 V
Weight according to EPTA Procedure 01/2003	3.9 kg
A-weighted emission sound pressure level ¹⁾	93 dB (A)
A-weighted emission sound power level ¹⁾	104 dB (A)
Arbour	20 mm
Base material	Wood and wood sandwich
Base plate - length	298 mm
Base plate - width	137 mm
Base plate dimensions (LxW)	298 x 137 mm
Battery type	Li-ion

¹⁾ according to EN 60745

3

Ordering designation	Package contents	Sales pack quantity	Item number
SCW 22-A box	1x Cordless circular saw SCW 22-A	1 pc	423166

Cordless circular saw SCM 22-A


CPC

KEY APPLICATIONS & ADVANTAGES

- Cutting channels and pipes on the jobsite quickly, with the highest possible accuracy
- Cutting openings in sheet metal in heating and air conditioning installation work
- Cutting sandwich panels, mesh and corrugated sheet metal
- More than 50 cuts in MQ41 channel possible with one battery charge
- Weight of less than 4 kg for best handling and ease of use

Technical data

Rated voltage	21.6 V
Weight according to EPTA Procedure 01/2003	4 kg
A-weighted emission sound pressure level ¹⁾	77 dB (A)
A-weighted emission sound power level ¹⁾	88 dB (A)
Arbour	20 mm
Base material	Metal and metal sandwich
Base plate - length	248 mm
Base plate - width	127 mm
Base plate dimensions (LxW)	248 x 127 mm
Battery type	Li-ion

¹⁾ according to EN 60745

Ordering designation	Package contents	Sales pack quantity	Item number
SCM 22-A cas	1x Cordless circular saw SCM 22-A, 1x Circ. saw blade SC-C MU 165x20 z40 A(20), 1x Case	1 pc	2024449

Cordless reciprocating saw for heavy-duty demolition with 22V battery featuring a keyless blade clamp and low vibration for smooth cutting WSR 22-A



KEY APPLICATIONS & ADVANTAGES

- Cutting metal pipes and conduits
- Cutting reinforcing bars, threaded rods and metal profiles
- Cutting window frames, woodwork and plastics
- Makes about twice as many cuts in metal per battery charge as other reciprocating saws of the same class
- Unique Active Vibration Reduction (AVR): the low-vibration vertical gearing system and spring-cushioned contact shoe greatly reduce vibration and thus enable smooth, easy cutting

Technical data

Rated voltage	21.6 V
Weight according to EPTA Procedure 01/2003	3.8 kg
A-weighted emission sound pressure level ¹⁾	82 dB (A)
A-weighted emission sound power level ¹⁾	93 dB (A)
Active Vibration Reduction	Yes
Base material	Metal, Wood and plastics
Battery type	Li-ion
Blade clamp	1/2" keyless
Deadman switch	Yes
Dimensions (LxWxH)	492 x 96 x 196 mm

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
WSR 22-A cas	1x Cordless reciprocating saw WSR 22-A assy, 1x Case	1 pc	404151

Cordless reciprocating saw WSR 36-A



KEY APPLICATIONS & ADVANTAGES

- Fast cutting in wood
- Cutting pipes overhead or in difficult-to-reach locations
- Wood and metal demolition
- Revolutionary D-grip and ergonomically positioned controls for superior handling in all working positions
- Low weight and compact design for maximum mobility even in tight spaces

Technical data









Rated voltage	36 V
Weight according to EPTA Procedure 01/2003	4.37 kg
A-weighted emission sound pressure level ¹⁾	90 dB (A)
A-weighted emission sound power level ¹⁾	101 dB (A)
Active Vibration Reduction	Yes
Base material	Metal, Wood, Mineral
Battery type	Li-ion
Blade clamp	1/2" keyless
Dimensions (LxWxH)	440 x 92 x 224 mm
Orbital action	No

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
WSR 36-A cas	1x Cordless reciprocating saw WSR 36-A, 1x Case	1 pc	213996

Accessories for Cordless saws

Ordering designation		WSR 22-A	SCW 22-A	SCM 22-A	WSR 36-A	Sales pack quantity	Item number
Battery charger C 4/36-350 230V box		■	■	■	■	1 pc	2028875
5.2 Fast Charge Combo		■		■		1 pc	3545209
Adapter for pipe cutting For the WSR 900-PE, 1250-PE, 1400-PE and WSR 36-A		■			■	1 pc	378888
Battery charger C 4/36-90 230V box		■	■	■		1 pc	2015761
Battery pack B 22/2.6 Li-ion		■		■		1 pc	2110532
Battery pack B 22/3.3 Li-Ion		■	■	■		1 pc	2007431
Battery pack B 22/5.2 Li-ion		■		■		1 pc	2110409
Battery pack B 36/3.0 Li-Ion					■	1 pc	418009
Guide rail WGS 1400-2			■			1 pc	338155
Parallel guide W-ASC PA85 WSC 85			■			1 pc	315675
Rail adapter SC 70W-A22			■			1 pc	2089216
Rail adapter SCM 22-A			■			1 pc	2098868
Rail adapter SCW/WSC			■			1 pc	437401

Cordless angle grinder AG 125-A22



KEY APPLICATIONS & ADVANTAGES

- Finishing
- Demolition
- Cutting and grinding steel and other metals
- Best ergonomic design and safety features of all comparable tools on the market (disc brake, ATC, automatic off)
- 30-40 % higher performance and battery capacity than competitors' tools

Technical data

Disk diameter	125 mm
Max cutting depth	34 mm
Spindle thread	14 mm
Active torque control	Yes
Active Vibration Reduction	No
Weight according to EPTA Procedure 01/2003	2.7 kg
Battery type	Li-ion
Deadman switch	Yes



Ordering designation	Package contents	Sales pack quantity	Item number
AG 125-A22	1x Cordless grinder AG 125 1x Case	1 pc	

Accessories for Cordless angle grinders

Ordering designation	AG 125-A22	Sales pack quantity	Item number
Battery pack B 22/3.3 Li-Ion	■	1 pc	2007431

Cordless 14V LED work light/lamp SFL 14-A



KEY APPLICATIONS & ADVANTAGES

- Providing illumination in dark environments
- Rugged, simple design - easy to use and carry, takes up little space in a toolbox
- Energy-efficient LED technology for extra-long battery life and bright, even light



Technical data

Battery type	Li-ion
Voltage	14.4 V
LED lamp power	3 W
Light output	190 lm
Beam angle	28.1 °
Operating time with 3.0/3.3 Ah Li-ion battery	6.5 h
Cordless Power Care - CPC	Yes
On/off switch	Yes
Height	87 mm
Length	100 mm

3

Ordering designation

Cordless lamp SFL 14-A box

Sales pack quantity

1 pc

Item number

426115

Cordless lamp SFL 22-A



KEY APPLICATIONS & ADVANTAGES

- Providing illumination in dark environments
- Rugged, simple design - easy to use and carry, takes up little space in a toolbox
- Energy-efficient LED technology for extra-long battery life and bright, even light



Technical data

Battery type	Li-ion
Voltage	21.6 V
LED lamp power	3 W
Light output	190 lm
Beam angle	28.1 °
Operating time with 3.0/3.3 Ah Li-ion battery	13 h
Cordless Power Care - CPC	Yes
On/off switch	Yes
Height	87 mm
Length	127 mm

Ordering designation

Cordless lamp SFL 22-A box

Sales pack quantity

1 pc

Item number

426117

Cordless lamp SFL 36-A



KEY APPLICATIONS & ADVANTAGES

- Mechanical installations
- Electrical installation
- Interior finishing
- Rugged, simple design - easy to use and carry, takes up little space in a toolbox
- Energy-efficient LED technology for extra-long battery life and bright light



Technical data

Battery type	Li-ion
LED lamp power	3 W
Light output	190 lm
Beam angle	28.1 °
Operating time with 3.0/3.3 Ah Li-ion battery	20 h
Cordless Power Care - CPC	Yes
On/off switch	Yes
Height	87 mm
Length	187 mm
Packaging	Cardboard

Ordering designation

Cordless lamp SFL 36-A box






Sales pack quantity

1 pc

Item number

2026734

Accessories for Cordless Lamps

Ordering designation		SFL 14-A	SFL 22-A	SFL 36-A	Sales pack quantity	Item number
Battery charger C 4/36-350 230V box				■	1 pc	2028875
Battery charger C 4/36-90 230V box		■	■		1 pc	2015761
Battery pack B 14/1.6 Li-Ion		■			1 pc	426174
Battery pack B 14/3.3 Li-Ion		■			1 pc	426175
Battery pack B 22/1.6 Li-Ion			■		1 pc	426177
Battery pack B 22/3.3 Li-Ion			■		1 pc	2007431
Battery pack B 36/3.0 Li-Ion				■	1 pc	418009

Dispenser HDE 500-A22

KEY APPLICATIONS & ADVANTAGES

- Injection of Hilti HIT adhesive mortar for fastening anchor rods and rebars in concrete and masonry
- Serial fastenings and/or injection in deep holes
- No need for external power source supply
- Easy injection even at low temperatures
- Dose adjustment knob for accurate and controlled dispensing

Technical data

Dispenser, setting tool, accessory, tester type	Dispensers
Battery type	22 V
Dispenser type	Battery
Power source type	22 V battery platform


CPC

Ordering designation	Weight	Package contents	Sales pack quantity	Item number
HDE 500-A22 CR/CB cas	2.2 kg	1x Dispenser HDE 500-A22 EU assy, 1x Cassette 500ml black, 1x Cassette 500ml red, 1x Case	1 pc	2005637

Accessories for Cordless Dispensers

Ordering designation		HDE 500-A22	Sales pack quantity	Item number
Battery charger C 4/36-90 230V box		■	1 pc	2015761

Hammer drill bit 4 - 6 mm TE-C



KEY APPLICATIONS & ADVANTAGES

- Drilling holes for metal and plastic anchors
- 2 cutting edges with direct helix transition for faster and more constant drilling progress
- Optimized tip geometry and rugged helix transition for longer lifetime



SDS plus

Technical data

Base material	Concrete, Brick, Masonry, Some types of natural stone
Tool type	All tools with TE-C (SDS-plus) chuck
Working mode	Hammer drilling, Drilling only

Ordering designation	Diameter	Length	Working length	Sales pack quantity	Item number
TE-C 5/11 MP8	5 mm	110 mm	50 mm	8 pc	2037053
TE-C 5/16 MP8	5 mm	160 mm	100 mm	8 pc	2037054
TE-C 6/11 MP8	6 mm	110 mm	50 mm	8 pc	2037056
TE-C 6/16 MP8	6 mm	160 mm	100 mm	8 pc	2037057
TE-C 8/11 MP8	8 mm	110 mm	50 mm	8 pc	2037063
TE-C 8/16 MP8	8 mm	160 mm	100 mm	8 pc	2037064
TE-C 8/21 MP8	8 mm	210 mm	150 mm	8 pc	2037065
TE-C 10/16 MP8	10 mm	160 mm	100 mm	8 pc	2037068
TE-C 10/21 MP8	10 mm	210 mm	150 mm	8 pc	2037069
TE-C 12/16 MP8	12 mm	160 mm	100 mm	8 pc	2037072
TE-C 12/21 MP8	12 mm	210 mm	150 mm	8 pc	2037073
TE-C 12/31 MP8	12 mm	310 mm	250 mm	8 pc	2037074
TE-C 14/21 MP8	14 mm	210 mm	150 mm	8 pc	2037077
TE-C 14/31 MP8	14 mm	310 mm	250 mm	8 pc	2037078
TE-C 16/16 MP8	16 mm	160 mm	100 mm	8 pc	2037080
TE-C 16/21 MP8	16 mm	210 mm	150 mm	8 pc	2037081
TE-C 16/31 MP8	16 mm	310 mm	250 mm	8 pc	2037082

Hammer drill bit sets (metric) TE-CX



KEY APPLICATIONS & ADVANTAGES

- Drilling holes for metal anchors in reinforced and unreinforced concrete
- Drilling holes for post-installed rebar connections
- Drilling drainage holes for drying out buildings
- New solid carbide head for less wear and more holes with the accuracy required for setting anchors
- Thanks to its innovative solid carbide head featuring gradient technology, the TE-CX drill bit is capable of drilling through steel rebars without any problem



SDS plus

Technical data

Base material	Reinforced concrete, Concrete, Brick, Masonry
Tool type	All tools with TE-C (SDS-plus) chuck
Working mode	Hammer drilling, Drilling only

Ordering designation	Package contents	Sales pack quantity	Item number
TE-CX (6) M1 set	1x Hammer drill bit TE-CX 5/12, 2x Hammer drill bit TE-CX 6/17, 1x Hammer drill bit TE-CX 8/17, 1x Hammer drill bit TE-CX 10/17, 1x Hammer drill bit TE-CX 12/17	1 pc	411214
TE-CX (6) M1 set	1x Hammer drill bit TE-CX 5/12, 2x Hammer drill bit TE-CX 6/17, 1x Hammer drill bit TE-CX 8/17, 1x Hammer drill bit TE-CX 10/17, 1x Hammer drill bit TE-CX 12/17	1 pc	411214

Hammer drill bit, multipack, 5 - 7 mm TE-CX



KEY APPLICATIONS & ADVANTAGES

- Drilling holes for metal anchors in reinforced and unreinforced concrete
- New solid carbide head for less wear and more holes with the accuracy required for setting anchors
- Innovative solid carbide head featuring the gradient technology for easy drilling through steel rebars



Technical data

Connection end	TE-C
Base material	Reinforced concrete, Concrete, Brick, Masonry
Tool type	All tools with TE-C (SDS-plus) chuck
Working mode	Hammer drilling, Drilling only

Ordering designation	Sales pack quantity	Item number
TE-CX 8/17	1 pc	409176
TE-CX 8/22	1 pc	409177
TE-CX 10/17	1 pc	409188
TE-CX 10/22	1 pc	409189
TE-CX 10/27	1 pc	409190
TE-CX 10/47	1 pc	409192
TE-CX 10/61	1 pc	409193
TE-CX 12/12	1 pc	409196
TE-CX 12/17	1 pc	409197
TE-CX 12/22	1 pc	409198
TE-CX 12/27	1 pc	409199
TE-CX 12/47	1 pc	409201
TE-CX 12/61	1 pc	409202
TE-CX 14/17	1 pc	409205
TE-CX 14/22	1 pc	409206
TE-CX 14/37	1 pc	409208
TE-CX 15/17	1 pc	409211
TE-CX 16/17	1 pc	409214
TE-CX 16/22	1 pc	409215
TE-CX 16/27	1 pc	409216
TE-CX 16/47	1 pc	409217
TE-CX 18/22	1 pc	421956
TE-CX 18/32	1 pc	421960
TE-CX 18/48	1 pc	421961
TE-CX 20/22	1 pc	421963
TE-CX 20/32	1 pc	421965
TE-CX 20/48	1 pc	421966
TE-CX 22/27	1 pc	421968
TE-CX 22/48	1 pc	421969
TE-CX 24/27	1 pc	421971
TE-CX 25/27	1 pc	421977
TE-CX 28/27	1 pc	421981
TE-CX 28/48	1 pc	421983
TE-CX 25/48	1 pc	422660
TE-CX 6/17	1 pc	433789
TE-CX 5/12 MP8	8 pc	2021990
TE-CX 5/15 MP8	8 pc	2021991
TE-CX 5/17 MP8	8 pc	2021992
TE-CX 6/12 MP8	8 pc	2021997
TE-CX 6/17 MP8	8 pc	2021998
TE-CX 6/22 MP8	8 pc	2021999
TE-CX 8/12 MP8	8 pc	2022002
TE-CX 8/17 MP8	8 pc	2022003
TE-CX 8/22 MP8	8 pc	2022004
TE-CX 8/27 MP8	8 pc	2022005
TE-CX 10/17 MP8	8 pc	2022008
TE-CX 10/22 MP8	8 pc	2022009
TE-CX 10/27 MP8	8 pc	2022010
TE-CX 12/17 MP8	8 pc	2022012
TE-CX 12/22 MP8	8 pc	2022013
TE-CX 12/27 MP8	8 pc	2022014
TE-CX 6/17 MP32	32 pc	2022045
TE-CX 8/17 MP32	32 pc	2022049
TE-CX 10/22 MP32	32 pc	2022053
TE-CX 10/27 MP32	32 pc	2022054
TE-CX 12/22 MP32	32 pc	2022056

SDS plus (TE-C) hollow drill bit, automatic hole cleaning solution for Hilti SafeSet systems, for drilling in reinforced concrete TE-CD



KEY APPLICATIONS & ADVANTAGES

- Drilling holes for anchoring structural steel connections (e.g. steel columns, beams)
- Drilling holes for structural connections with post-installed rebars
- Drilling holes for anchoring secondary steel structures (e.g. staircases, steel ledgers)
- Drilling and hole cleaning in one step
- Optimum hole cleaning for consistent anchor setting


SAFE-SET

SDS plus

Technical data

Connection end	TE-C
Base material	Reinforced concrete, Concrete
Tool type	All tools with TE-C (SDS-plus) chuck
Working mode	Hammer drilling

Ordering designation	Diameter	Length	Working length	Sales pack quantity	Item number
TE-CD 12/33	12 mm	330 mm	200 mm	1 pc	2018940
TE-CD 14/37	14 mm	370 mm	240 mm	1 pc	2018942
TE-CD 16/37	16 mm	370 mm	240 mm	1 pc	2018945
TE-CD 18/37	18 mm	370 mm	240 mm	1 pc	2018946

HSS ground drill bit for drilling small-diameter holes in metal HSS



KEY APPLICATIONS & ADVANTAGES

- Drilling in unalloyed and medium-alloyed steel
- High-speed steel drill bit with split point, 135° tip angle
- Ideal for use with Hilti cordless tools

Technical data

Base material	Metal, Steel, Medium alloyed steel, Unalloyed steel, Aluminium
Material coating/plating/finish	HSS M2 steel
Tool type	SF 14-A, SF 22-A, SFC 14-A, SFC 22-A, SFH 14-A, SFH 22-A, UD 16, UD 30, UH 700
Working mode	Drilling only

Ordering designation	Diameter	Length	Working length	Wrench size	Package contents	Sales pack quantity	Item number
HSS 2,0x49mm "MP10	2 mm	49 mm	24 mm			10 pc	304900
HSS 3,0x61mm "MP10	3 mm	61 mm	33 mm			10 pc	304903
HSS 3,2x65mm "MP10	3.2 mm	65 mm	36 mm			10 pc	304904
HSS 3,5x70mm "MP10	3.5 mm	70 mm	39 mm			10 pc	304908
HSS 4,0x75mm "MP10	4 mm	75 mm	43 mm			10 pc	304910
HSS 4,2x75mm "MP10	4.2 mm	75 mm	43 mm			10 pc	304912
HSS 4,5x80mm "MP10	4.5 mm	80 mm	47 mm			10 pc	304914
HSS 5,0x86mm "MP10	5 mm	86 mm	52 mm			10 pc	304916
HSS 5,2x86mm "MP10	5.2 mm	86 mm	52 mm			10 pc	304917
HSS 5,5x93mm "MP10	5.5 mm	93 mm	57 mm			10 pc	304920
HSS 6,0x93mm "MP10	6 mm	93 mm	57 mm			10 pc	304923
HSS 6,5x101mm "MP10	6.5 mm	101 mm	63 mm			10 pc	304924
HSS 7,0x109mm "MP10	7 mm	109 mm	69 mm			10 pc	304925
HSS 8,0x117mm "MP10	8 mm	117 mm	75 mm			10 pc	304927
HSS 8,5x117mm "MP10	8.5 mm	117 mm	75 mm			10 pc	304928
HSS 9,0x125mm "MP10	9 mm	125 mm	81 mm			10 pc	304929
HSS 10,50x133mm "MP5	10.5 mm	133 mm	87 mm			5 pc	304932
HSS 10,0x133mm "MP10	10 mm	133 mm	87 mm			10 pc	304931
HSS 11,0x142mm "MP5	11 mm	142 mm	94 mm			5 pc	304933
HSS 12,0x151mm "MP5	12 mm	151 mm	101 mm			5 pc	304935
HSS 13,0x151mm "MP5	13 mm	151 mm	101 mm			5 pc	304937
HSS 16,0x178mm	16 mm	178 mm	178 mm	120 mm	1x Twist drill bit HSS 16x178, 1x Hanger clip DYT 36x74 16/1 red	1 pc	2066676
HSS 18,0x191mm	18 mm	191 mm	130 mm		1x Twist drill bit HSS 18x191	1 pc	2066678

HSS ground drill bit set for drilling small-diameter holes in metal HSS sets



KEY APPLICATIONS & ADVANTAGES

- High-speed steel drill bit with split point, 135° tip angle
- Ideal for use with Hilti cordless tools

Technical data

Base material	Steel, Aluminium, Carbon steel, Metal, Medium alloyed steel, Unalloyed steel
Material composition	HSS M2 steel
Tool type	SF 14-A, SF 22-A, SFC 14-A, SFC 22-A, SFH 14-A, SFH 22-A, UD 16, UD 30, UH 700
Working mode	Drilling only

Ordering designation

Ordering designation	Sales pack quantity	Item number
HSS 2-8 set	1 pc	213950
HSS 1-10 kit	1 pc	304938
HSS 1-13 kit	1 pc	304939

Stepper bit for drilling or enlarging holes of different sizes in metal HSS SB



KEY APPLICATIONS & ADVANTAGES

- Drilling thin metal sheets in electrical and building applications
- High-speed steel drill bit with a split point for accurate drilling
- Diameter markings on the inner edge for greater convenience

Technical data

Base material	Metal
Material composition	HSS M2 steel
Tool type	SF 14-A, SF 18, SF 22-A, SFC 14-A, SFC 18, SFC 22-A, SFH 14-A, SFH 18, SFH 22-A
Working mode	Drilling only

Ordering designation

Ordering designation	Length	Working length	Sales pack quantity	Item number
4-20	73 mm	48 mm	1 pc	304983
M10-M40	97 mm	72 mm	1 pc	304984

MetalCut bimetal hole saw adapter and accessories HS-ME



KEY APPLICATIONS & ADVANTAGES

- Quick-change system for hole saws and centring bit
- Convenient quick release of the centring bit from the hole saw
- Quick and reliable hole saw attachment and release

Technical data

Base material	Steel and stainless steel, Aluminium
Connection end	Hexagonal
Material composition	HSS M35 steel
Tool type	SF 14-A, SF 22-A, SFH 14-A, SFH 22-A
Working mode	Drilling only

Ordering designation

Ordering designation	Sales pack quantity	Item number
Hole saw arbor MetalCut	1 pc	216214
HSS-Co	5 pc	206040

MetalCut bimetal hole saw for cutting holes of 16-83 mm diameter in steel and metal HS-ME



KEY APPLICATIONS & ADVANTAGES

- Cutting holes in stainless steel, steel and metal sheets
- HSS cobalt (8%) alloy for longer lifetime and higher performance
- Special tooth design for fast, accurate cutting

Technical data	
Working length	28 mm
Base material	Steel, Non-ferrous metal
Tool type	SF 14-A, SF 22-A, SFH 14-A, SFH 22-A
Working mode	Drilling only

Ordering designation	Diameter	Sales pack quantity	Item number
20mm-25/32" MetalCut	20 mm	1 pc	417555
25mm-1" MetalCut	25 mm	1 pc	417560
30mm-1 3/16" MetalCut	30 mm	1 pc	417565
32mm-1 1/4" MetalCut	32 mm	1 pc	417567
33mm-1 5/16" MetalCut	33 mm	1 pc	417568
35mm-1 3/8" MetalCut	35 mm	1 pc	417569
51mm-2" MetalCut	51 mm	1 pc	417577
64mm-2 1/2" MetalCut	64 mm	1 pc	417581

Spade bit set for fast drilling of shallow holes in wood WDB-S sets



KEY APPLICATIONS & ADVANTAGES

- Drilling small- to medium-diameter holes in soft or hard wood
- Ideal for drilling overhead or for use with SID impact tools
- Self-feeding threaded tip allows drilling with less effort and reduces vibration
- Spur and reamer edges create cleaner holes

Technical data	
Working length	100 mm
Base material	Wood
Connection end	1/4 in hexagonal
Tool type	SF 14-A, SF 18, SF 22-A, SFH 14-A, SFH 18, SFH 22-A, SID
Working mode	Drilling only

Ordering designation	Package contents	Sales pack quantity	Item number
WDB-S-H6 16-32 set	1x Spade bit WDB-S-H6 16x152, 1x Spade bit WDB-S-H6 18x152, 1x Spade bit WDB-S-H6 20x152, 1x Spade bit WDB-S-H6 22x152, 1x Spade bit WDB-S-H6 25x152, 1x Spade bit WDB-S-H6 32x152, 1x Spade bit WDB-S-H1/4 E6	1 pc	2025582

Auger bit for smoothly drilling deep holes in wood WDB A



KEY APPLICATIONS & ADVANTAGES

- Accurate drilling in wood, heavy timber and nail-embedded wood, also suitable for deep drilling
- Self-feeding threaded tip helps pull the bit through the wood
- Large flutes for efficient chip removal

Technical data	
Diameter	22 mm
Length	460 mm
Working length	400 mm
Base material	Wood
Connection end	Hexagonal
Tool type	SF 14-A, SF 18, SF 22-A, SFC 14-A, SFC 18, SFC 22-A, SFH 14-A, SFH 18, SFH 22-A, UD 16, UD 30, UH 700
Working mode	Drilling only

Ordering designation	Sales pack quantity	Item number
22x400/460	1 pc	305002



Short 1/2" impact sockets SI-S 1/2" S



KEY APPLICATIONS & ADVANTAGES

- Tightening nuts and bolts
- Driving and removing wood screws
- Anchor fastening
- Two detent holes to increase connection accuracy between the socket and 1/2" anvil
- Dual detent bevels

Technical data

Connection end size	12.7 mm
Drive connection	1/2 in square, female
Drive head	6-point, hex, female
Material coating/plating/finish	Black phosphate
Material composition	Impact-grade chrome molybdenum steel
Tool type	SIW

Ordering designation	Wrench size	Length	Sales pack quantity	Item number
SI-S 1/2"-13 S	13 mm	40 mm	1 pc	2070371
SI-S 1/2"-19 S	19 mm	40 mm	1 pc	2070376
SI-S 1/2"-21 S	21 mm	40 mm	1 pc	2070377
SI-S 1/2"-22 S	22 mm	40 mm	1 pc	2070378
SI-S 1/2"-24 S	24 mm	40 mm	1 pc	2070379
SI-S 1/2"-27 S	27 mm	40 mm	1 pc	2070380
SI-S 1/2"-30 S	30 mm	40 mm	1 pc	2070381
SI-S 1/2"-32 S	32 mm	40 mm	1 pc	2070382
SI-S 1/2"-36 S	36 mm	50 mm	1 pc	2070383

Long 1/2" impact sockets SI-S 1/2" L



KEY APPLICATIONS & ADVANTAGES

- Tightening nuts and bolts
- Driving and removing wood screws
- Anchor fastening
- Two detent holes to increase connection accuracy between the socket and 1/2" anvil
- Dual detent bevels

Technical data

Length	80 mm
Connection end size	12.7 mm
Drive connection	1/2 in square, female
Drive head	6-point, hex, female
Material coating/plating/finish	Black phosphate
Material composition	Impact-grade chrome molybdenum steel
Tool type	SIW

Ordering designation	Wrench size	Sales pack quantity	Item number
SI-S 1/2"-17 L	17 mm	1 pc	2070392
SI-S 1/2"-19 L	19 mm	1 pc	2070394
SI-S 1/2"-21 L	21 mm	1 pc	2070395
SI-S 1/2"-22 L	22 mm	1 pc	2070396
SI-S 1/2"-24 L	24 mm	1 pc	2070397
SI-S 1/2"-27 L	27 mm	1 pc	2070398
SI-S 1/2"-30 L	30 mm	1 pc	2070399
SI-S 1/2"-32 L	32 mm	1 pc	2070400
SI-S 1/2"-36 L	36 mm	1 pc	2070401

Impact socket set 1/2" S-NSD



KEY APPLICATIONS & ADVANTAGES

- Tightening nuts and bolts
- Driving and removing wood screws
- Anchor fastening
- Two detent holes to increase connection accuracy between the socket and 1/2" anvil
- Dual detent bevels

Technical data

Connection end size	12.7 mm
Drive connection	1/2 in square, female
Drive head	6-point, hex, female
Material coating/plating/finish	Black phosphate, Silver
Material composition	Impact-grade chrome molybdenum steel
Tool type	Impact tools, SIW
Weight	0.75 kg

Ordering designation	Package contents	Sales pack quantity	Item number
S-NSD 13-15 set	1x Impact socket S-NSD 1/2"-13 S, 1x Impact socket S-NSD 1/2"-15 S, 1x Impact socket S-NSD 1/2"-13 L, 1x Impact socket S-NSD 1/2"-15 L	1 pc	408429

Torque bar S-TB



KEY APPLICATIONS & ADVANTAGES

- For setting HSA stud anchors with maximum accuracy and productivity
- Reliable ETA approved system using SIW 14-A, 22-A or 22T-A impact wrench
- No more over or undertorquing of HSA stud anchors

Technical data	
Base material	Concrete (uncracked)
Connection end size	12.7 mm
Drive connection	1/2 in square, female
Drive head	1/2 in, square, male
Material coating/plating/finish	Black
Material composition	Impact-grade chrome molybdenum steel
Tool type	Impact tools, SIW

Ordering designation	Weight	Sales pack quantity	Item number
S-TB HSA M8	0.11 kg	1 pc	423774
S-TB HSA M10	0.12 kg	1 pc	423775
S-TB HSA M12	0.12 kg	1 pc	423776
S-TB HSA M16	0.13 kg	1 pc	423777

Super performance thin abrasive cutting disc AC-D SP-line



KEY APPLICATIONS & ADVANTAGES

- Cutting steel and stainless steel pipes, rods, profiles and metal sheets
- High performance and extra long lifetime
- Low-burring, heat-reducing disc, ideal for cutting stainless steel

Technical data	
Disclaimer	Use angle grinder with double-sided guard
Arbour	22.23 mm
Blade / disc line	Special performance
Grain type	Aluminium oxide
Max. permitted speed	12250 rpm
Application	Cutting
Base material	Steel and stainless steel
Tool type	Angle grinder

Ordering designation	Blade diameter	Disc diameter	Blade thickness	Sales pack quantity	Item number
AC-D 115x1.2 SP	117 mm	115 mm	1.2 mm	25 pc	2047357
AC-D 125 (5'') SP CAG	125 mm	125 mm	1 mm	25 pc	2126634



Super performance flap disc for light grinding AF-D SP-line



KEY APPLICATIONS & ADVANTAGES

- Flat version is used with lower contact pressure for light surface grinding on steel and stainless steel
- Convex version is ideal for use with high contact pressure for light grinding on welds and edges
- Self-sharpening effect due to the lamellar structure of the aluminium-zirconia
- Very long lifetime thanks to the poly (cotton and nylon mix) backing material

Technical data

Arbour	22.23 mm
Blade / disc shape	Convex
Blade / disc line	Special performance
Grain type	Zirconium
Max. grain size	60
Backing	Resin fibre
Application	Light grinding
Base material	Steel and stainless steel
Grain density - for others	60
Tool type	Angle grinder

Ordering designation	Blade diameter	Disc diameter	Max. permitted speed	Sales pack quantity	Item number
AF-D 115 G60 RF CX SP	115 mm	115 mm	13300 rpm	10 pc	438326
AF-D 125 G60 RF CX SP	125 mm	125 mm	12200 rpm	10 pc	438329

Circular saw blades for metal SC-C M



KEY APPLICATIONS & ADVANTAGES

- Steel blade: Cold cutting in ferrous metal and structural panels (channel iron, pipe, angle iron, steel plate, threaded rod, rebar, sandwich panel)
- Cutting with Hilti SC-C M blades is much faster than traditional methods
- Hilti SC-C M blades feature a hardened steel disc and carbide tips with a unique shape for exceptional wear resistance

Technical data

Blade diameter	165 mm
Arbour	20 mm
Kerf width	1.6 mm
Blade thickness	1.2 mm
Blade material	HW
Max. cutting depth	57 mm
Sales pack qty.	1
Colour code	Blue

Ordering designation	Base material	Number of teeth	Blade type	Max. rpm	Other packaging sizes	Tooth type	Sales pack quantity	Item number
SC-C MU 165x20 z40 A	Ferrous metal	40	Steel	4200	2070234	WZ	1 pc	2014797
SC-C MS 165 AL	Non-ferrous metal	48	Aluminium	9500	2070235	FZ/TR	1 pc	2023990

Circular saw blades for fast, precise cutting in wood SCB Wood



KEY APPLICATIONS & ADVANTAGES

- Universal use for rip and cross cutting in plywood, formwork boards, OSB, particle/chipboard, MDF, wood composites, solid wood (hard and soft) and construction timber
- Clean cross cutting in plywood, formwork boards, OSB, particle/chipboard, MDF, wood composites, solid wood (hard and soft) and plastics
- Smoother and more precise, using less power – these blades let you cut for longer
- Ultra-thin-kerf technology and a friction-reducing coating for clean, smooth cutting and outstanding battery life

Technical data

Blade type	Universal
Application range	Rip and cross cuts in wooden boards (plywood, formwork, OSB, particle/chipboard, MDF, wood composites and solid wood (hard and soft)) and construction timber
Number of teeth	24
Tooth type	WZ
Blade material	HW
Sales pack qty.	5
Colour code	Yellow

Ordering designation	Base material	Blade diameter	Arbour	Blade thickness	Kerf width	Max. cutting depth	Sales pack quantity	Item number
SCB WU 190x30 z24A (5)		190 mm	30 mm	1 mm	1.5 mm	70 mm	5 pc	2145816
SCB WU 165x20 z24 A(5)	Wood	165 mm	20 mm	1 mm	1.5 mm	57 mm	5 pc	2070222
SCB WU 230x30 z24(5)	Wood	230 mm	30 mm	1.6 mm	2.5 mm	85 mm	5 pc	2070230

SDS Max (TE-Y) standard narrow-flat chisel for controlled breaking TE-Y-RFM



SDS max

KEY APPLICATIONS & ADVANTAGES

- Optimum chisel geometry for high performance
- Inductive hardening for long service life

Technical data

Base material	Concrete, Brick, Masonry, Some types of natural stone
Tool type	All tools with TE-Y (SDS-max) connection
Width	26 mm

Ordering designation	Length	Sales pack quantity	Item number
TE-Y RFM 28 MP10	280 mm	10 pc	373600
TE-Y RFM 40 MP10	400 mm	10 pc	340767
TE-Y RFM 50 MP10	500 mm	10 pc	340765

SDS Max (TE-Y) standard wide-flat chisel for surface work and layer removal TE-Y-RSPM



SDS max

KEY APPLICATIONS & ADVANTAGES

- Chipping
- Smoothing
- Cleaning
- Optimum chisel geometry for high performance
- Inductive hardening for long service life

Technical data

Base material	Asphalt, Concrete, Brick
Length	280 mm
Tool type	All tools with TE-Y (SDS-max) connection
Width	50 mm

Ordering designation	Sales pack quantity	Item number
TE-Y RSPM 5/28	1 pc	337812

SDS Max (TE-Y) standard pointed chisel for light demolition TE-Y-RSM



SDS max

KEY APPLICATIONS & ADVANTAGES

- Optimum chisel geometry for high performance
- Inductive hardening for long service life

Technical data

Base material	Concrete, Brick, Masonry, Some types of natural stone
Tool type	All tools with TE-Y (SDS-max) connection

Ordering designation	Length	Sales pack quantity	Item number
TE-Y-RSM 28 MP10	280 mm	10 pc	373599
TE-Y-RSM 40 MP10	400 mm	10 pc	340766
TE-Y-RSM 50 MP10	500 mm	10 pc	340764

Battery charger C4/36-90



KEY APPLICATIONS & ADVANTAGES

- Ideal for universal use: charges all Hilti 14V, 22V and 36V Li-Ion batteries
- Designed to help protect batteries from low voltage and adverse charging conditions

Technical data

Cordless Power Care - CPC	Yes
---------------------------	-----



CPC

Ordering designation	Package contents	Sales pack quantity	Item number
Battery charger C 4/36-90 230V box	1x Battery charger C 4/36-90 230V	1 pc	2015761

Battery charger C4/36-350



KEY APPLICATIONS & ADVANTAGES

- Fastest charger for Hilti 36V batteries

Technical data

Cordless Power Care - CPC	Yes
---------------------------	-----



CPC

Ordering designation	Package contents	Sales pack quantity	Item number
Battery charger C 4/36-350 230V box	1x Battery charger C 4/36-350 220V	1 pc	2028875

Battery charger C 4/12-50 230V box



Technical data

Accessory type	Charger
Battery type	Li-ion
Battery charge status display	Yes
Voltage	12 V

Ordering designation	Package contents	Sales pack quantity	Item number
Battery charger C 4/12-50 230V box	1x Battery charger C 4/12-50 230V	1 pc	2077004

Battery pack B 12/2.6



Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	2.6 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/12-50 battery charger	35 min
Charging time with C4/36-350 battery charger	35 min
Number of cells	3
Voltage	12 V

Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 12/2.6	1x Battery pack B 12/2.6	1 pc	2077976

Battery pack B 14/1.6 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology with cells of outstanding quality and individual electronic control for high performance and long life under the toughest conditions
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	1.6 Ah
Charging time with C4/36-350 battery charger	21 min
Number of cells	4
Voltage	14.4 V


CPC

Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 14/1.6 Li-ion	1x Battery pack B 14/1.6 Li-ion	1 pc	426174

Battery pack B 22/2.6 Li-ion



Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	2.6 Ah
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	35 min
Number of cells	6
Voltage	21.6 V


CPC

Ordering designation	Sales pack quantity	Item number
Battery pack B 22/2.6 Li-ion	1 pc	2110532

22 V 5.2 Ah Li-ion battery B22/5.2



Technical data

Accessory type	Battery
Cordless Power Care - CPC	Yes
Battery capacity	5.2 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	35 min
Number of cells	12
Voltage	21.6 V



Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 22/5.2 Li-ion		1 pc	2110409
5.2 Fast Charge Combo	1x Battery charger C 4/36-350 220V, 2x Battery pack B 22/5.2 Li-ion	1 pc	3545209

Battery B 14/3.3 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology with cells of outstanding quality and individual electronic control for high performance and long life under the toughest conditions
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	3.3 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	23 min
Number of cells	8
Voltage	14.4 V



Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 14/3.3 Li-ion	1x Battery pack B 14/3.3 Li-ion	1 pc	426175

22 V 1.6 Ah Li-ion battery B 22/1.6 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology featuring cells of outstanding quality with individual electronic charging control for high performance and long life in the toughest environments
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	1.6 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	21 min
Number of cells	6
Voltage	21.6 V

Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 22/1.6 Li-ion	1x Battery pack B 22/1.6 Li-ion	1 pc	426177

22 V 3.3 Ah Li-ion battery B 22/3.3 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology featuring cells of outstanding quality with individual electronic charging control for high performance and long life under the toughest conditions
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	3.3 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	31 min
Number of cells	12
Voltage	21.6 V

Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 22/3.3 Li-ion	1x Battery pack B 22/3.3 Li-ion	1 pc	2007431

36 V 3.0 Ah Li-ion battery B 36/3.0 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology featuring cells of outstanding quality with individual electronic charging control for high performance and long life in the toughest environments
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	3.0 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	24 min
Number of cells	20
Voltage	36 V

Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 36/3.0 Li-ion	1x Battery pack B 36/3.0 Li-ion	1 pc	418009

36 V 3.9 Ah Li-ion battery B 36/3.9 Li-ion



KEY APPLICATIONS & ADVANTAGES

- CPC technology featuring cells of outstanding quality with individual electronic charging control for high performance and long life in the toughest environments
- Features a protective system to prevent overheating, overloading and deep discharge

Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	3.9 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	44 min
Number of cells	30
Voltage	36 V



Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 36/3.9 Li-Ion	1x Battery pack B 36/3.9 Li-Ion	1 pc	401594

36 V 6.0 Ah Li-ion battery B 36 6.0 Li-ion



KEY APPLICATIONS & ADVANTAGES

- Compatible with the the TE 30-A combi-hammer and the SFL 36-A flashlight
- Compatible with the TE 30-A combi-hammer, SFL 36-A flashlight and VC 20/40-U(M)-Y vacuum cleaner
- Robust 36V Li-ion battery with a capacity of 6.0 Ah
- CPC technology featuring cells of outstanding quality with individual electronic charging control for high performance and long life in the toughest environments

Technical data

Accessory type	Battery
Battery type	Li-ion
Cordless Power Care - CPC	Yes
Battery capacity	6.0 Ah
Deep discharge protection	Yes
Battery charge status display	Yes
Charging time with C4/36-350 battery charger	42 min
Number of cells	30
Voltage	36 V



Ordering designation	Package contents	Sales pack quantity	Item number
Battery pack B 36/6.0 Li-Ion	1x Battery pack B 36/6.0 Li-Ion assy	1 pc	2018896

Tool Kit



Technical data

Accessory type	Toolbox
----------------	---------

Ordering designation	Package contents	Sales pack quantity	Item number
Case Tool Kit-A22 Typ 039		1 pc	2064776
Case TE/SF/SI Combo Typ 039		1 pc	365136
Case WSR/SFH/SIW 039		1 pc	423661
Case TE/SF/SI/AG/WSR Type 047 kit	1x Case	1 pc	2045753

Softbag For power tools



KEY APPLICATIONS & ADVANTAGES

- Hilti tools can be carried with great convenience
- Heavy-duty, easy-pull zipper

Technical data

Accessory type	Softbag
----------------	---------

Ordering designation	Sales pack quantity	Item number
Toolbag large	1 pc	2008518
Toolbag small	1 pc	434910

Eye protection for general use Safety glasses / goggles



KEY APPLICATIONS & ADVANTAGES

- Optimal eye coverage and wrap-around protection
- High-impact resistant polycarbonate lenses, additional curvature at the upper edge providing an integrated brow guard

Technical data

Disclaimer	Hilti does not issue recommendations for selection of the appropriate eye protection equipment which always depends on the relevant application and environment. Selection of the appropriate eye protection equipment is therefore solely the responsibility of the user.
-------------------	--

Ordering designation	Height	Length	Weight	Sales pack quantity	Item number
Safety glasses PP EY-GU C HC/AF clear	5 mm	15 mm	0.03 kg	1 pc	2065445
Safety glasses PP EY-GU B AF blue	5 mm	15 mm	0.03 kg	1 pc	2065447



On-board vacuum system for convenient dust collection TE DRS-4-A



KEY APPLICATIONS & ADVANTAGES

- Virtually dust-free drilling with the 2nd generation TE 4-A22/18
- Approved for use in low-asbestos drilling applications (German BGI 664, BT 12)
- Built-in motor for maximum system efficiency
- Provides 100% suction power from the start

Technical data

Weight according to EPTA Procedure 01/2003	1 kg
Base material	Concrete
Depth gauge	Yes
Height	230 mm
Length	319 mm
Weight class	1 kg
Width	84 mm
Working mode	Hammer drilling

Ordering designation	Package contents	Sales pack quantity	Item number
Dust removal system TE DRS-4-A box	1x Dust removal system TE DRS-4-A	1 pc	2098487

On-board vacuum system for convenient dust collection TE DRS-6-A



KEY APPLICATIONS & ADVANTAGES

- Virtually dust-free drilling with the TE 6-A36-AVR
- Approved for use in low-asbestos drilling applications (by German BGI 664, BT 12)
- Built-in motor for maximum system efficiency
- Provides 100% suction power from the beginning

Technical data

Rated input power	60 W
Weight according to EPTA Procedure 01/2003	1 kg
Depth gauge	Yes
Height	230 mm
Length	319 mm
Width	84 mm

Ordering designation	Package contents	Sales pack quantity	Item number
Dust removal system TE DRS-6-A box	1x Dust removal system TE DRS-6-A, 1x Protective cover	1 pc	2040914

Universal wet and dry cordless and corded vacuum cleaner with automatic filter cleaning – tank capacity 21 liters – class M VC 20-U(M)-Y



KEY APPLICATIONS & ADVANTAGES

- Removing dust created by drilling, slitting, grinding, cutting and coring
- Removing wet coring slurry
- General cleaning and removal of wet and dry materials
- Corded and cordless wet and dry vacuum cleaner
- Integrated universal battery charger for all Hilti Li-ion batteries (14V, 22V, 36V)

Technical data

Container capacity	21 l
Dust capacity	23 kg
Water capacity	13.5 l
A-weighted emission sound pressure level ¹⁾	70 dB (A)
Hose diameter	36 mm
Brushless motor	No
Hose length	4650 mm
Length	530 mm
Max. vacuum pressure	220 mbar
Operating temperature range	-10 - 45 °C

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
VC 20-U-Y 230V	1x Univ. vacuum cleaner VC 20-U-Y 230V	1 pc	2044306

Universal wet and dry cordless and corded vacuum cleaner with automatic filter cleaning – tank capacity 36 liters – class M VC 40-U(M)-Y



KEY APPLICATIONS & ADVANTAGES

- Removing dust created by drilling, slitting, grinding, cutting and coring
- Removing wet coring slurry
- Charging all Hilti Li-ion batteries (14V, 22V, 36V)
- Corded and cordless wet and dry vacuum cleaner
- Integrated universal battery charger for all Hilti Li-ion batteries (14V, 22V, 36V)

Technical data









Container capacity	36 l
Dust capacity	40 kg
Water capacity	25 l
A-weighted emission sound pressure level ¹⁾	70 dB (A)
Hose diameter	36 mm
Brushless motor	No
Hose length	4650 mm
Length	530 mm
Max. vacuum pressure	220 mbar
Power (max.)	1.2 kW

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
VC 40-U-Y 230V	1x Univ. vacuum cleaner VC 40-U-Y 230V	1 pc	2044382

Accessories for Cordless Vacuum Cleaners

Ordering designation		VC 20-U(M)-Y	VC 40-U(M)-Y	Sales pack quantity	Item number
Dust bag VC 40 (10) plastic			■	10 pc	203852
Adapter plate VC 20/40		■	■	1 pc	2044211
Battery pack B 36/3.0 Li-Ion		■	■	1 pc	418009
Battery pack B 36/3.9 Li-Ion		■	■	1 pc	401594
Battery pack B 36/6.0 Li-Ion		■	■	1 pc	2018896
Bend VC 20/40/60 assy		■	■	1 pc	203875
Dust bag VC 20 (10) plastic		■		10 pc	203854
Floor nozzle VC 20/40/60		■	■	1 pc	203873
Push bar VC 20		■		1 pc	2044214
Push bar VC 40			■	1 pc	2047174
Tool box VC 20/40		■	■	1 pc	2044212

Cordless drywall screwdriver SD 5000-A22



KEY APPLICATIONS & ADVANTAGES

- Fastening drywall boards to metal or wood framing on walls and ceilings
- Fastening metal track to metal track (framing)
- Fastening particle board (chipboard) to wood framing
- With the speed and power of a corded tool: speed 5000/min, torque 9.5Nm
- High battery capacity and very short charging time: 21.6V/3.3 Ah lithium-ion battery featuring Hilti Cordless Power Care (CPC)

Technical data

A-weighted emission sound power level¹⁾	82 dB (A)
Max. torque	10 Nm
Dimensions (LxWxH)	253 x 99 x 235 mm
Weight according to EPTA Procedure 01/2003	2.1 kg
Uncertainty for the given sound level¹⁾	3 dB (A)
A-weighted emission sound pressure level¹⁾	71 dB (A)
Approvals	CB - certificate, EMC - Report, EN 55014 / EN 61000, IEC 60745 / EN 60745, NTR - report (Notification of Test Results)
Battery type	Li-ion
Chuck type	1/4 in hexagon socket
Control switch lock	Yes

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
SD 5000-A22 box	1x Cordl. dryw. screwdriver SD 5000-A22, 1x Driver bit S-B PH2 25/1" IF, 1x Bit holder S-BH M 50/2"	1 pc	403196

Cordless metal construction screwdriver ST 1800-A22



KEY APPLICATIONS & ADVANTAGES

- Driving self-drilling and self-tapping screws in various materials including steel, aluminium and wood
- Fastening profile metal sheets
- Fastening sandwich panels
- High-performance cordless screwdriver with the features of a corded tool, specially designed for metal construction work
- Compact and well-balanced design with practical and comfortable in-line grip

Technical data

Battery energy	56.16 Wh
Dimensions (LxWxH)	252 x 94 x 268 mm
Battery capacity	3.3 Ah
Battery type	Li-ion
Max. torque	12 Nm
A-weighted emission sound pressure level¹⁾	70 dB (A)
Control switch lock	Yes
Weight according to EPTA Procedure 01/2003	2.5 kg
Uncertainty for the given sound level¹⁾	3 dB (A)
A-weighted emission sound power level¹⁾	81 dB (A)

¹⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
ST 1800-A22 box	1x Cordl. metal screwdr. ST 1800-A22, 1x Socket wrench insert S-NSD 8, 1x Cap	1 pc	437866